

InfineaTab Mini

Microcontroller	Cortex-M3
Buttons	1 scan button
Magnetic Card Reader	Triple track bi-directional Encryption head (optional)
Contactless Reader (optional)	ISO/IEC 14443 Type A MIFARE Mini, MIFARE Classic 1K, MIFARE Classic 4K, MIFARE Ultralight, MIFARE Ultralight C, MIFARE Plus 2K, MIFARE Plus 4K, MIFARE DESFire ISO/IEC 14443 Type B ISO/IEC 15693 JIS X 6319-4 - FeliCa ISO/IEC 18000-3 - NFC
Contactless Payments (optional)	VISA payWave MasterCard Contactless American Express ExpressPay Discover D-Pas
2D Barcode Reader	Opticon MDI3000 - 752 x 480 CMOS (optional) Honeywell N4680 - 640 x 480 Global Shutter (optional) Honeywell N5780 - 1280 x 800 Global Shutter (optional)
Connectors	USB Mini port Lightning connector (cradle) SAM card slot (optional)
Wired Communication	RS-232, USB (pass-through sync)
Bluetooth (optional)	BT version 3.0 power class 2
Device Compatibility	iPad mini, iPad mini 2, iPad mini 3, iPad mini 4, iPad Air, iPad Air 2, iPad Pro, iPhone 6 Plus, iPhone 6s Plus, iPhone 7 Plus, iPhone 8 Plus
LED Indication	Battery status, Contactless payment status
Audio Features	Electromagnetic buzzer
Power Supply	DC 5 V through USB, DC 5 V through contact pins
Battery	Rechargeable Li-Ion Battery 3.7 V, 1100 mAh
Reliability	1,000,000 magnetic card swipes
Certificates	CE, FCC, PCI PTS 3.x, EMV Level 1, EMV Level 2, EMV Level 1 Contactless, Apple Mfi
Dimension W x D x H	103 x 88 x 24 mm
Weight	140 g
Operational Temperature	-10 °C to 40 °C / 5 to 90% RH
Storage Temperature	-20 °C to 50 °C / 5 to 90% RH
Box Contents	InfineaTab Mini device, 90 cm USB Type-A to Mini cable
Compatible Accessories	Charger (GT1), 5-unit charger (GT5), Holster, Metal Stand

InfineaTab Mini offers a choice between the SAM card slot and Bluetooth options.