

LineaPro 5

Microcontroller	Cortex-M3
Buttons	1 scan button, 1 battery status button
Magnetic Card Reader	Triple track bi-directional, Encryption head (optional)
Contactless Reader (optional)	ISO/IEC 14443 Type A MIFARE Mini, MIFARE Classic 1K, MIFARE Classic 4K, MIFARE Ultralight, MIFARE Ultralight C, MIFARE Plus 2K, MIFARE Plus 4K, MIFARE DESFire ISO/IEC 14443 Type B ISO/IEC 15693 JIS X 6319-4 - FeliCa ISO/IEC 18000-3 - NFC
1D Barcode Reader	Opticon MDL-1000 Laser Scan Engine (optional)
2D Barcode Reader	Newland EM3090 - 752 x 480 CMOS (optional) Intermec EA30 - 752 x 480 CMOS (optional) Honeywell N3680 - 640 x 480 CMOS (optional) Honeywell N4680 - 640 x 480 Global Shutter (optional) Honeywell N5780 - 1280 x 800 Global Shutter (optional)
Connectors	USB Mini port Lightning connector (cradle) Power transfer to phone
Wired Communication	RS-232 USB (pass-through sync)
Bluetooth (optional)	BT version 2.0 power class 2
Device Compatibility (select cradle)	iPhone 5, iPhone 5s, iPhone SE, iPod touch 5th generation, iPod touch 6th generation
LED Indication	Battery status
Audio Features	Electromagnetic buzzer
Power Supply	DC 5 V through USB, DC 5 V through contact pins
Battery	Rechargeable Li-Ion Battery 3.7 V, 1300 mAh
Reliability	1,000,000 magnetic card swipes
Certificates	CE, FCC, PCI PTS 3.x, Apple Mfi
Dimension W x D x H	69 x 142 x 22 mm (1D BCR) 69 x 142 x 27 mm (2D BCR)
Weight	120 g
Operational Temperature	-10 °C to 40 °C / 5 to 90% RH
Storage Temperature	-20 °C to 50 °C / 5 to 90% RH
Drop Tested	1.5 m, faces and edges
Box Contents	LineaPro 5 device, 90 cm USB Type-A to Mini cable
Compatible Accessories	Charger (GT1), 5-unit charger (GT5), Holster, Pistol Grip