

LineaPro 7 Industrial



Microcontroller	Cortex-M3
Buttons	2 scan buttons
Contactless Reader (optional)	ISO/IEC 14443 Type A MIFARE Mini MIFARE Classic 1K MIFARE Classic 4K MIFARE Ultralight MIFARE Ultralight C MIFARE Plus 2K MIFARE Plus 4K MIFARE DESFire ISO/IEC 14443 Type B ISO/IEC 15693 JIS X 6319-4 - FeliCa ISO/IEC 18000-3 - NFC
2D Barcode Reader	Opticon MDI-4000 - 640 x 480 CMOS (optional) Zebra SE4710 - 1280 x 800 CMOS (optional) Zebra SE4750SR - 1280 x 960 CMOS (optional) Zebra SE4750MR - 1280 x 960 CMOS (optional)
Connectors	USB Type-C port Lightning connector (cradle) Power transfer to phone SAM card slot (optional)
Wired Communication	RS-232 USB (pass-through sync)
Bluetooth (optional)	BT version 3.0 power class 2
Device Compatibility	iPhone 8, iPhone 7, iPhone 6, iPhone 6s
Audio Features	Electromagnetic buzzer
Power Supply	DC 5 V through USB, DC 5 V through contact pins
Battery	Rechargeable Li-Ion Battery 3.6 V, 2400 mAh Fuel Gauge
Certificates	IP65 CE
Dimension W x D x H	75 x 158 x 26 mm
Weight	148 g
Operational Temperature	-10 °C to 40 °C / 5 to 90% RH
Storage Temperature	-20 °C to 50 °C / 5 to 90% RH
Box Contents	LineaPro 7 Industrial device 90 cm USB Type-A to Type-C cable
Compatible Accessories	Charger (GT1) 5-unit charger (GT5) Dual charger Multi Battery Charger (MBC5)