

Alpha 203 dpi

Printing Mechanism	Direct line thermal printer
Printing Resolution	203 dpi
Printing Speed	200 mm per second at 203 dpi
Printing Width	108 mm at 203 dpi
Max Printing Length	2286 mm at 203 dpi
Memory	128 MB RAM, 256 MB Flash
Sensors	Print Frame Open Detect, Ribbon End Detect, Paper Out Detect, TPH Over Heating Detect, 2 Fixed See-through sensor, Full Range Reflective Sensor
Paper Type	Continuous, Gap, Black Mark, Perforation
Paper Width	26 to 118 mm
Paper Thickness	60 to 250 µm
Max Roll Diameter	127 mm
Spool Diameter	12, 25, 38 mm
Ribbon Type	Wax, Resin, Wax/Resin
Ribbon Width	30 to 110 mm
Ribbon Max Length	100 m
Drivers	Windows 7, 8, 10, server 2008, 2012
Barcode Types	Code 39, Code 93, EAN 8/13 (add on 2 & 5), UPC A/E (add on 2 & 5), I 2 of 5, Codabar, Code 128 (subset A, B, C), EAN 128, MSI, Plessey, Telepen, GS1 DataBar, Standard 2 of 5, Industrial 2 of 5, Code 11, Code 49 PDF417, Data matrix code, QR code, Micro PDF417, Aztec code
Wired Communication	USB, RS-232, LAN, Bluetooth (optional), Wireless (optional)
Buttons	On/Off button, Feed button
Power Supply	AC 100 to 240 V, DC 24 V, 2 A
Operational temperature	5 °C to 50 °C, 25 to 85% RH
Storage temperature	40 °C to 60 °C, 10 to 90% RH
Certificates	CE EMC (EN 55022 Class B), FCC EMC (Class A), CCC, RoHS
Dimension W x D x H	201 x 252 x 181 mm
Weight	1800 g
Additional Features	Auto cutter, Automatic label peeler, External paper holder

