



🚌 Innovating Perfection 🚁

DP-15	
Printer Mechanism	Direct line thermal printer Citizen MLT-288
Max Printing Speed	12 lines per sec
Paper Width	57 mm (42 characters per line)
Paper Thickness	60 μm
Roll Diameter	55 mm
Paper Loading	Easy paper loading
Operator Display	Graphic LCD, 2 lines x 16 characters (96 x 18 px)
Customer Display	Alpha-numeric LCD, 2 lines x 16 characters Graphic LCD, 2 lines x 16 characters (96 x 18 px)
Keyboard and Buttons	33 Keys
PLU Database	2500 PLUs 22 characters name length
Inventory Groups	9
Departments	9
Operators	30 (8 active)
TAX Groups	8
Fiscal Memory	Non-volatile, 1825 reports
Journal	Electronic Journal
Printable Logo	384 x 96 to 384 x 336 dots (8 dot step)
Payment Types	Cash, check, card, credit (programmable) Cash with alternative currency
Barcode Types	EAN 13, EAN 8, UPC, Printed by electronic scales
Max Number of Sales per Receipt	Over 120
Connectivity	2 x RS-232C (for Barcode reader, Digital scale, External customer display or PC) 1 x Drawer control port Bluetooth (optional) GPRS (optional)
Power Supply	AC 110 to 240 V, 50 to 60 Hz, DC 9 V, 5 A
Battery	Rechargeable Li-Ion battery 7.4 V, 2000 mAh
Dimensions W x D x H	160 x 222 x 63 mm 160 x 222 x 114 mm (with customer display)
Weight	665 g









