





🚌 Innovating Perfection 🚁

DP-50 Plus	
Printer Mechanism	Direct line thermal printer Citizen MLT-289
Max Printing Speed	12 lines per sec
Paper Width	57 mm (42 characters per line) 2 x 28 mm (18 characters per line)
Paper Thickness	60 to 72 μm
Roll Diameter	65 mm 40 mm (2 rolls)
Paper Loading	Easy paper loading
Operator Display	Graphic LCD 2 lines x 16 characters (98 x 16 px)
Customer Display	Alpha-numeric LCD 2 lines x 16 characters (optional)
Keyboard and Buttons	29 keys
PLU Database	15 000 PLUs (trade mode) 5 000 PLUs (restaurant mode) 22 characters name length
Inventory Groups	99
Departments	99
Operators	30
TAX Groups	8
Fiscal Memory	Non-volatile, 1825 reports
Journal	on Paper Roll or Electronic Journal
Printable Logo	384 x 96 dots
Payment Types	Cash, check, credit card, coupon
Barcode Types	EAN-13, EAN-8, UPC, Printed by electronic scales
Max Number of Sales per Receipt	Over 300
Connectivity	1 x RS 232C (REG mode for Barcode Reader, Digital scale, External customer display or PC)
Power Supply	AC 110 to 240 V, 50 to 60 Hz, DC 9 V, 1 A
Battery	Rechargeable Li-Ion battery 7.4 V, 2000 mAh
Reliability	Keeps the clock at least 90 days after switching off the ECR
Dimensions W x D x H	88 x 194 x 67 mm 88 x 219 x 67 mm (with customer display)
Weight	570 g
Compatible Accessories	Holster Car Power Adapter





