



## 🚌 Innovating Perfection 👟

DP-500	
Printer Mechanism	Direct line thermal printer Citizen MLT-389
Max Printing Speed	12 lines per sec
Paper Width	57 mm 2 x 38 mm (24 characters per line)
Paper Thickness	60 to 72 μm
Roll Diameter	65 mm 50 mm (2 rolls)
Paper Loading	Easy paper loading
Operator Display	Graphic LCD, 128 x 64 px with backlight
Customer Display	Alpha-numeric LCD, 2 lines x 16 characters
Keyboard and Buttons	38 Keys
PLU Database	7500 PLUs
Inventory Groups	10
Departments	16
Operators	30 Operators names and passwords
TAX Groups	8
Fiscal Memory	Non-volatile ROM, 2000 reports
Journal	on Paper Roll or Electronic Journal
Payment Types	Cash, check, coupon Cash with alternative currency (EUR)
Barcode Types	EAN-13, EAN-8, UPC
Connectivity	3 x programmable RS-232C - PC (Online via RS232C and Bluetooth, with remote PC via GPRS through FTP Server, offline via SD Card), Barcode Reader, Electronic Scale 1 x Drawer control port
Power Supply	AC 110 to 240 V, 50 to 60 Hz, DC 12 V, 2.5 A
Battery	Rechargeable Li-Ion battery 7.4 V, 2000 mAh (optional)
Dimensions W x D x H	244 x 277 x 118 mm
Weight	1400 g
Compatible Accessories	External keyboard 50 keys





