

Electronic Cash Register DP-55 Plus



DP-55 Plus represents the classical concept for an Electronic Cash Register. It is built around a powerful ARM processor and offer to the customers a great variety of functions and report generating. Suitable for midsize shops, restaurants etc.



DP-55 Plus	
Printer Mechanism	Direct line thermal printer Citizen MLT4280KS
Max Printing Speed	12 lines per sec
Paper Width	57 mm (42 characters per line) 2 x 28 mm (18 characters per line)
Paper Thickness	60 to 72 µm
Roll Diameter	65 mm 40 mm (2 rolls)
Paper Loading	Easy paper loading
Operator Display	Graphic LCD, 4 lines x 22 characters (128 x 32 px)
Customer Display	Alpha-numeric LCD, 2 lines x 16 characters
Keyboard and Buttons	33 Keys
PLU Database	30 000 PLUs 22 characters name length Max Q-ty per item 99 999.999 kg
Inventory Groups	99
Departments	99
Operators	30 (30 active)
TAX Groups	8
Fiscal Memory	Non-volatile, 2400 reports
Journal	on Paper Roll or Electronic Journal
Printable Logo	384 x 96 to 384 x 336 dots
Payment Types	Cash, check, card, credit Cash with alternative currency (USD or EUR)
Barcode Types	EAN-13, EAN-8, UPC, Printed by electronic scales
Max Number of Sales per Receipt	Over 300
Connectivity	2 x RS-232C (for Barcode reader, Digital scale, External customer display, Bank terminal, External keyboard or PC) 1 x Ethernet port (LAN) 1 x Drawer control port 1 x Barcode reader port (with power supply) GPRS (optional)
Power Supply	AC 110 to 240 V, 50 to 60 Hz, DC 12 V, 2.5 A
Battery	Rechargeable Li-Ion battery 7.4 V, 2000 mAh (optional)
Reliability	Keeps the clock at least 90 days after switching the ECR off
Dimensions W x D x H	168 x 243 x 69 mm 168 x 243 x 104 mm (with customer display)
Weight	850 g