

Electronic Cash Register DP-55 Plus



DP-55 Plus represents the classical concept for an Electronic Cash Register. It is built around a powerful ARM processor and offer to the customers a great variety of functions and report generating. Suitable for midsize shops, restaurants etc.



| DP-55 Plus | |
|---------------------------------|---|
| Printer Mechanism | Direct line thermal printer Citizen MLT4280KS |
| Max Printing Speed | 12 lines per sec |
| Paper Width | 57 mm (42 characters per line) 2 x 28 mm (18 characters per line) |
| Paper Thickness | 60 to 72 µm |
| Roll Diameter | 65 mm 40 mm (2 rolls) |
| Paper Loading | Easy paper loading |
| Operator Display | Graphic LCD, 4 lines x 22 characters (128 x 32 px) |
| Customer Display | Alpha-numeric LCD, 2 lines x 16 characters |
| Keyboard and Buttons | 33 Keys |
| PLU Database | 30 000 PLUs 22 characters name length Max Q-ty per item 99 999.999 kg |
| Inventory Groups | 99 |
| Departments | 99 |
| Operators | 30 (30 active) |
| TAX Groups | 8 |
| Fiscal Memory | Non-volatile, 2400 reports |
| Journal | on Paper Roll or Electronic Journal |
| Printable Logo | 384 x 96 to 384 x 336 dots |
| Payment Types | Cash, check, card, credit Cash with alternative currency (USD or EUR) |
| Barcode Types | EAN-13, EAN-8, UPC, Printed by electronic scales |
| Max Number of Sales per Receipt | Over 300 |
| Connectivity | 2 x RS-232C (for Barcode reader, Digital scale, External customer display, Bank terminal, External keyboard or PC) 1 x Ethernet port (LAN) 1 x Drawer control port 1 x Barcode reader port (with power supply) GPRS (optional) |
| Power Supply | AC 110 to 240 V, 50 to 60 Hz, DC 12 V, 2.5 A |
| Battery | Rechargeable Li-Ion battery 7.4 V, 2000 mAh (optional) |
| Reliability | Keeps the clock at least 90 days after switching the ECR off |
| Dimensions W x D x H | 168 x 243 x 69 mm 168 x 243 x 104 mm (with customer display) |
| Weight | 850 g |