

DPP-250



Buttons	On/Off button, Feed button
Printing Mechanism	Direct line thermal printer
Printing Resolution	203 x 203 dpi (8 x 8 dpmm)
Printing Width	48 mm (384 dots)
Printing Speed	80 mm per second
Printable Font Sizes	Font A - 12 x 24 dots, Font B - 9 x 16 dots
Loadable Font Sizes	Font C - 24 x 24 dots, Font D - 9 x 16 dots, Font E - 24 x 24 dots (optional), Font F - 24 x 24 dots Chinese (optional)
Printable Logo	1 Black and White (384 x 248 dots)
Printable Barcode Types	Codabar, Code 128, Code 39, Code 93, EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, PDF417, QR Code
Paper Width	58 mm
Max Roll Diameter	45 mm
Paper Loading	Easy paper loading
Emulation	ESC/POS
Magnetic Card Reader (optional)	Triple track bi-directional
Smart Card Reader (optional)	Friction type
Connectors	USB Mini port, 2.5 mm audio jack for serial communication
Wired Communication	RS-232, USB (device)
OS Compatibility	iOS, Android, Windows
Bluetooth	BT 3.0, Transceiver, Frequency of operation from 2402MHz to 2480MHz, Antenna gain +2dBi
LED Indication	Battery low, Charging, Paper end, Cover open, Overheating, BT, Reading
Power Supply	AC 100 to 240 V, 50 to 60 Hz, DC 9 V, 1 A
Battery	Rechargeable Li-Ion battery, 7.4 V, 1150 mAh
Reliability	50 km (thermal head), 1,000,000 magnetic card swipes, 500,000 chip card cycles, 20,000 lines with one charge
Certificates	CE
Dimension W x D x H	86 x 113 x 57 mm
Weight	295 g
Operational Temperature	-10 to 60 °C, 30 to 85 % RH
Storage Temperature	-20 to 60 °C, 0 to 90 % RH
Drop Tested	1.2 m, faces and edges
Compatible Accessories	Holster, Belt clip, Car power adapter