

# DPP-350



<b>Buttons</b>	On/Off button, Feed button
<b>Printing Mechanism</b>	Direct line thermal printer
<b>Printing Resolution</b>	203 x 203 dpi (8 x 8 dpmm)
<b>Printing Width</b>	72 mm (576 dots)
<b>Printing Speed</b>	60 mm per second
<b>Printable Logo</b>	1 Black and White (576 x 248 dots)
<b>Printable Barcode Types</b>	Codabar, Code 128, Code 39, Code 93, EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, PDF417, QR Code
<b>Paper Width</b>	78 and 58 mm
<b>Max Roll Diameter</b>	50 mm
<b>Paper Loading</b>	Easy paper loading
<b>Emulation</b>	ESC/POS
<b>Magnetic Card Reader (optional)</b>	Triple track bi-directional
<b>Smart Card Reader (optional)</b>	Landing type
<b>Contactless Reader (optional)</b>	NFC-A, ISO 14443 Type A, NFC-B, ISO 14443 Type B, NFC-F, Felica, NFC-V, ISO 15693
<b>Connectors</b>	USB Mini port
<b>Wired Communication</b>	RS-232, USB (device)
<b>OS Compatibility</b>	iOS, Android, Windows
<b>Bluetooth (optional)</b>	BT 3.0
<b>Wireless (optional)</b>	Wi-Fi IEEE 802.11 b
<b>LED Indication</b>	Battery low, Charging, Paper end, Cover open, Overheating, BT, Reading
<b>Power Supply</b>	AC 100 to 240 V, 50 to 60 Hz, DC 9 V, 1 A
<b>Battery</b>	Rechargeable Li-Ion battery, 7.4 V, 2000 mAh
<b>Reliability</b>	50 km (thermal head), 1,000,000 magnetic card swipes, 500,000 chip card cycles, 30,000 lines with one charge
<b>Certificates</b>	CE, FCC, MFi
<b>Dimension W x D x H</b>	108 x 111 x 63 mm
<b>Weight</b>	400 g
<b>Operational Temperature</b>	-10 to 40 °C, 30 to 85 % RH
<b>Storage Temperature</b>	-20 to 60 °C, 0 to 90 % RH
<b>Drop Tested</b>	1.2 m, faces and edges
<b>Compatible Accessories</b>	Holster, Belt clip, Car power adapter