

DPP-450



Buttons	On/Off button, Print button, Feed button
Display	128 x 64 px Monochrome LCD, Backlight
Printing Mechanism	Direct line thermal printer
Printing Resolution	203 x 203 dpi (8 x 8 dpmm)
Printing Width	104 mm (832 dots)
Printing Speed	150 mm per second
Printable Logo	1 Black and White (832 x 248 dots)
Printable Barcode Types	Codabar, Code 128, Code 39, Code 93, EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, PDF417, QR Code
Paper Type	Thermal paper roll (optional), Label Roll (optional)
Sensors	Black mark, Label gap, Peeled label (optional), Cutter (optional)
Paper Width	50 to 115 mm
Max Roll Diameter	58 mm
Paper Loading	Easy paper loading
Post Printing Features	Label peeler
Emulation	ESC/POS
Contactless (optional)	NFC-A, ISO 14443 Type A, NFC-B, ISO 14443 Type B, NFC-F, Felica, NFC-V, ISO 15693
Connectors	USB Mini port
Wired Communication	RS-232, USB (device)
OS Compatibility	iOS, Android, Windows
Bluetooth (optional)	BT 3.0
Wireless (optional)	Wi-Fi IEEE 802.11 b
LED Indication	Battery low, Battery charging, Paper end, Cover open, Overheating
Power Supply	AC 100 to 240 V, 50 to 60 Hz, DC 19 V, 5.2 A
Battery	Rechargeable Li-Ion battery, 14.4 V, 2200 mAh
Reliability	50 km (thermal head), 15,000,000 lines (mechanism), 20,000 lines with one charge
Certificates	CE, FCC, MFi
Dimension W x D x H	157 x 138 x 67 mm
Weight	785 g
Operational Temperature	-15 to 50 °C, 30 to 85 % RH, -20 to 60 °C, 10 to 90 % RH (Storage)
Drop Tested	1.2 m, faces and edges
Compatible Accessories	Holster, Belt clip, Shoulder strap, Battery charger, Vehicle stand