EP-05

Printing Mechanism	Direct line thermal printer
Printing Resolution	203 x 203 dpi (8 x 8 dpmm)
Printing Width	48 mm (384 dots)
Printing Speed	80 mm per second
Printable Logo	384 × 384 dots
Printable Barcode Types	Codabar, Code 128, EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, GS1 DataBar Stacked, Omnidirectional, Stacked Omnidirectional, Truncated, Limited, PDF417, Micro PDF417, QR Code, Micro QR Code, MaxiCode, Data Matrix
Paper Width	58 mm
Max Roll Diameter	40 mm
Paper Loading	Easy paper loading
Emulation	ESC/POS
Connectors	Contact pins (cradle) 2 x USB Type-C ports
Wired Communication	USB
OS Compatibility	iOS Android Windows
Device Compatibility	BlueCash-05
Bluetooth	BT version 5.1 Low Energy
Audio Features	Electro-Magnetic Buzzer
Vibration Capabilities	
Power Supply	Charged via USB Type-C PD, 9 V, 2A
Battery	Li-Ion, 7.4 V, 1150 mAh
Dimension W x D x H	87 x 115 x 74 mm
Weight	270 g
Operational Temperature	0 °C to 45 °C / 10 to 90% RH
Storage temperature	-20 °C to 70 °C / 10 to 90% RH

