



🚌 Innovating Perfection 🚁

FP-600	
Printing Mechanism	Direct line thermal printer
Printing Width	54 mm (432 dots)
Printing Resolution	203 x 203 dpi (8 x 8 dpmm)
Max Printing Speed	37 lines per second
Printable Font Sizes	Font A - 12 x 24 dots (36 characters per line)
Printable Logo	1 Black and White (54 x 12 mm)
Printable Barcode Types	EAN-13, EAN-8, Code 128, Interleaved 2 of 5
Paper Type	Thermal paper rolls
Paper Width	58 mm
Paper Thickness	60 μm
Roll Max Diameter	60 mm
Paper Loading	Easy paper loading
Post Printing Features	Auto cutter
Emulation	Datecs Proprietary Fiscal Protocol
Connectivity	RS-232C Cash Drawer through RJ11 connector External Display through RJ11 connector GPRS Module (optional)
LED Indication	Paper end Overheating Power On Device Status
Keyboard and Buttons	On/Off button 2 function buttons
Power Supply	AC 100 to 240 V, 50 to 60 Hz, DC 24 V, 2 A
Reliability	100 million pulses, 100 km (Thermal head) 1 million cuts (Auto cutter)
Certificates	CE
Dimensions W x D x H	125 x 355 x 175 mm
Weight	2500 g
Operational temperature range	-10 to 40 °C, 35 to 85 % RH





