

FP-950

Printing Mechanism	Direct line thermal printer
Printing Width	72 mm (576 dots per line)
Printing Resolution	203 x 203 dpi (8 x 8 dpmm)
Printing Speed	230 mm per second
Printable Font Sizes	Font A (48 symbols per line) Font B (42 symbols per line)
Printable Barcode Types	UPC-A, UPC-E, Code 39, Code 93, Code 128, EAN 128, EAN 8, EAN 13, Interleaved 2 of 5, QR Code, PDF417
Paper Width	80 and 58 mm
Max Roll Diameter	83 mm
Paper Loading	Easy paper loading
Post Printing Features	Auto cutter
Buttons	6 function buttons
Display	Alphanumeric LCD, 3 lines of 24 symbols
Fiscal Memory	3650 reports
Fiscal Journal	Electronic Journal SD card
Printable Logo	1 Black and White (576 x 96 dots)
Sensors	Black mark
Connectors	RJ11 port (cash drawer), RJ45 port (Ethernet), USB Type-B port
Wired Communication	RS-232 USB (device)
Bluetooth	BT version 3.0
Wireless	Wi-Fi IEEE 802.11 b/g/n
Cellular Module	2G/3G/4G communication
LED Indication	Paper end, Cover open, Overheating, Auto cutter error
Audio Features	Electromagnetic buzzer
Power Supply	AC 100 to 240 V, 50 to 60 Hz, DC 24 V, 1.5 A
Battery	Rechargeable Li-Po battery, 3.7 V, 200 mAh
Dimension W x D x H	140 x 179 x 117 mm
Weight	1840 g
Operational Temperature	-10 to 40 °C, 35 to 85 % RH
Storage Temperature	-20 to 60 °C, 10 to 90 % RH

