

LineaPro 5 Industrial



Buttons	2 scan button, 1 battery status button, 1 reset device
Contactless Reader (optional)	ISO/IEC 14443 Type A MIFARE Mini, MIFARE Classic 1K, MIFARE Classic 4K, MIFARE Ultralight, MIFARE Ultralight C, MIFARE Plus 2K, MIFARE Plus 4K, MIFARE DESFire ISO/IEC 14443 Type B ISO/IEC 15693 JIS X 6319-4 - FeliCa ISO/IEC 18000-3 - NFC
2D Barcode Reader	Opticon MDI-4000 - 640 x 480 CMOS (optional) Honeywell N3680 - 640 x 480 CMOS (optional) Honeywell N4680 - 640 x 480 Global Shutter (optional) Honeywell N5780 - 1280 x 800 Global Shutter (optional)
Connectors	USB Type-C port Lightning connector (cradle) Power transfer to phone
Device Compatibility	iPod touch 7th generation
Audio Features	Electromagnetic buzzer
Power Supply	DC 5V through USB, DC 5V through single or 5 station charger
Battery	Rechargeable Li-Ion Battery 3.6 V, 2330 mAh, Fuel Gauge microcontroller
Reliability	1,000,000 magnetic card swipes
Dimension W x D x H	68 x 144 x 26 mm
Weight	151 g
Operational Temperature	-10 °C to 40 °C / 5 to 90% RH
Storage Temperature	-20 °C to 50 °C / 5 to 90% RH
Compatible Accessories	Charger (GT1), 5-unit charger (GT5), Holster, Dual charger (DC1)