

## Fiscal Printer TM-T260F

DATECS TM-T260 BGF is a new generation of fiscal printers offered by DATECS LTD. The printer uses a standard EPSON Line Thermal Printer TM-T260F to which Datecs engineers have added all their expertise in the design of fiscal equipment. As a result we can offer to our customers a full line of fiscal printers.

RIND

## $\Longrightarrow$ Innovating Perfection $\Longrightarrow$

| TM-T260F                      |   |   |     |   |          |
|-------------------------------|---|---|-----|---|----------|
| Printing Mechanism            | Direct line thermal printer   |   |     |   |          |
| Printing Width                | 56 mm (448 dots)  |   |     |   |          |
| Printing Resolution           | 203 x 203 dpi (8 x 8 dpmm)  |   |     | _ | $\vdash$ |
| Max Printing Speed            | 150 mm per second   |   | ╋╋╋ |   | Н        |
| Printable Font Sizes          | Font A - 11 x 24 dots<br>Font B - 9 x 17 dots   |   | HH  |   |          |
| Printable Logo                | Yes   |   |     |   |          |
| Printable Barcode Types       | 1D: EAN-13, EAN-8, UPC-A, UPC-E, Code 39, Code 128,<br>Interleaved 2 of 5, Codabar, Code 93         |   |     |   | П        |
| Paper Type                    | Thermal paper rolls   |   |     |   |          |
| Paper Width                   | 60 mm   |   |     |   |          |
| Paper Thickness               | 60 μm   |   |     |   |          |
| Roll Max Diameter             | 63 mm   |   |     |   |          |
| Paper Loading                 | Easy paper loading  |   |     |   |          |
| Post Printing Features        | Auto cutter   | _ |     |   |          |
| Fiscal Memory                 | Up to 4 MB  |   |     |   |          |
| Emulation                     | Datecs Proprietary Fiscal Protocol  | _ |     |   |          |
| Connectivity                  | RS-232C<br>USB 1.1<br>Cash Drawer through RJ11 connector<br>External Display through RJ11 connector |   |     |   |          |
| LED Indication                | On/Off<br>Paper end   |   |     |   |          |
| Keyboard and Buttons          | On/Off button<br>2 function buttons   |   |     |   |          |
| Power Supply                  | AC 100 to 240 V, 50 to 60 Hz, DC 24 V, 2 A  |   |     |   |          |
| Reliability                   | 15 million lines (Mechanism)<br>100 km (Thermal head)<br>1 million cuts (Auto cutter)               |   |     |   |          |
| Certificates                  | CE  |   |     |   |          |
| Dimensions W x D x H          | 140 x 300 x 200 mm  |   |     |   |          |
| Weight                        | 3500 g  |   |     |   |          |
| Operational temperature range | 5 to 45 °C, 10 to 85 % RH   |   |     |   |          |
| Storage temperature range     | -10 to 50 °C, 10 to 90 % RH   |   |     |   |          |



4 Datecs Str., Sofia 1592, Bulgaria tel: +359 2 8165 550, fax: +359 2 8165 565 e-mail: sales@datecs.bg, www.datecs.bg



