

# WPP-350



<b>Buttons</b>	On/Off button, 2 navigation buttons
<b>Display</b>	OLED Display
<b>Printing Mechanism</b>	Direct line thermal printer
<b>Printing Resolution</b>	203 x 203 dpi (8 x 8 dpmm)
<b>Printing Width</b>	72 mm (576 dots)
<b>Printing Speed</b>	80 mm per second
<b>Printable Font Sizes</b>	Font A - 12 x 24 dots, Font B - 9 x 16 dots
<b>Printable Barcode Types</b>	Codabar, Code 128, EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, GS1 DataBar Stacked, Omnidirectional, Stacked Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, PDF417, Micro PDF417, QR Code, Micro QR, Code, MaxiCode, Data Matrix
<b>Paper Width</b>	80 mm
<b>Max Roll Diameter</b>	50 mm
<b>Paper Loading</b>	Easy paper loading
<b>Emulation</b>	ESC/POS
<b>Connectors</b>	USB Type-C port
<b>Wired Communication</b>	USB (device)
<b>OS Compatibility</b>	iOS, Android, Windows
<b>Bluetooth (optional)</b>	BT version 4.2 Low Energy
<b>Wireless (optional)</b>	Wi-Fi IEEE 802.11 b/g/n
<b>LED Indication</b>	Paper end, Cover open, Overheating
<b>Audio Features</b>	Electromagnetic buzzer
<b>Power Supply</b>	AC 100 to 240 V, 50 to 60 Hz, DC 9 V, 1.3 A
<b>Battery</b>	Rechargeable Li-Ion battery, 7.4 V, 2000 mAh
<b>Reliability</b>	50 km (thermal head), IP54 (Internal test)
<b>Certificates</b>	CE, FCC, VCCI
<b>Dimension W x D x H</b>	106 x 122 x 61 mm
<b>Weight</b>	370 g
<b>Operational Temperature</b>	-10 to 50 °C, 20 to 80 % RH
<b>Storage Temperature</b>	-20 to 60 °C, 10 to 90 % RH
<b>Drop Tested</b>	1.2 m, faces and edges (Internal test)
<b>Other Box Contents</b>	90 cm USB Type-A to Type-C cable, DC 9 V, 1.3 A Power Adapter
<b>Compatible Accessories</b>	Belt clip